

# Thaimadam Machines

## Eight Colour Rotogravure Printing Machine (Standard)



### Optimized for fine performance

**Elegantly Designed** for Smooth and comfortable operation The basic design is made from the point of view of machine-operator and is user friendly. The print view and inspection is made easy by providing peculiar window for that purpose. Oil-dipped worm gear box for the transmission makes the machine run smoothly and silently. The air circulation through silent blowers makes the efficiency of the print drying faster and with less pressure on the substrate and reduced noise, and electrical power.

The initial tasks like loading of cylinders, loading of rolls, register synchronization are made easy through new mechanisms. Once printed cylinders can be reloaded and printed with out going through much of the register synchronization tasks and avoid wastage of substrate.

The feeding system is easily movable to in-between any printing units so that minimum run-length can be maintained in case of print jobs having lesser colours. The peculiar feeding mechanism makes the machine suitable to attach any kind of Web-Aligner or Web-Tension-Controls to the machine.

### Important features

**Cardridge loading of Feed Rolls**

**Insert ability to feed rolls in between printing units**

**Split ability of the machine**

**Universal Reversibility**

**Unique Viewing Window**

**Distributed Control Panel**

**Motorised Register Synchronization**

**For further details please visit**

[www.thaimadam.in](http://www.thaimadam.in) [www.thaimadam.com](http://www.thaimadam.com)

## **Cartridge Loading of Feed Rolls**

Feed rolls are usually heavy and occasionally is very difficult to mount on the normal machine. The mounting operation is done by either fixing on a shaft or on mounting shaft less holds. Both this operation requires lifting of the rolls and carrying on to the machine. For heavy rolls having more than 100 kg this operation is nightmare for the operators. But in Thaimadam Machines this operation is made simple. The mounting shaft is fixed to the core of the rolls and is mounted on the mounting cartridge at the place specified for the purpose away from the machine. Hydraulic jack mechanism or Chain pulley mechanism can be provided for lifting up the heavy rolls to place on the cartridge. Then the cartridge is carried to the machine on its wheels and slip inside the machine to fix it on the machine.

## **Insert ability to feed rolls in between printing units**

Each printing unit is having a separate roll feed mounting rails, placed just before the printing unit. Thus a normal Thaimadam Machines with six colour printing capability is having six feeding stations. This facility reduces the substrate length considerably and their by reduce the probable wastage. Even while the printing operation is going on, next feed roll can be mounted on the feed cartridge and made ready on the available nearest feed stations. When the running roll is finished the machine need be stopped only for seconds to start the next roll and get running. This mechanism reduces the idle time on the printing machine, for roll change. This type of feed mechanism helps to split the machine to act as two machines.

## **Split ability of the machine**

Thaimadam printing machine can be split into two to act as two separate printing machines. Thus on a six colours printing machine we can do either a single colour and a five colour job simultaneously OR a two colour and four colour job OR two three colour jobs simultaneously. The splitting operation is made very simple and requires only few minutes to make the machine ready for doing two print jobs and viz. This enable the machine to give double output.

## **Universal Reversibility**

The machine is universally reversible to print on both side of the printing format. To print on Poly film tubes to make poly bags both side printing is necessary. The cross-bar technology twilt the substate. The mechanism can be moved and placed in between any printing units so that the furhter progress of printing can be on the other side of the substrate. The adjustments to reverse the substrate is very easy and it does not require any mechanical miodification or change on the machine.

## **Unique Viewing Window**

In the conventional machines, the operator has to sit down and look upwards, leaning inside the machine to get a view of the printed format or the doctor blade assembly if anything goes wrong the operator has to face a lot of troubles to get a clear picture of this situation. Almost all the upper area constituting drying chamber is enclosed and cannot be see from outside. This problem is completely eliminated in Thaimadam Machines.

The design of the printing machine is made in such a way to provide a unique viewing window for the operator for inspection of the printing operation. The front portion of the drying chamber is opened up as a window and is protected by glass. The glass faced window provide easy view of the complete printing process at the same time protect hazardous solvent vapor. This enable the clear view of doctor blade assembly, impression rollers and the printed substrate. Inside the window is adequately lighted up so that the printing image is clearly visible to scrutinized its colour and print registers. This protects the operator from the hazardous vapor of ink and solvent. The appearance of the machine is made simple and elegant. The control panel is placed immediately near to the viewing window so that the operation and necessary correction can be done while viewing through the window.

## **Register Synchronization:**

The register synchronization (Calendaring) is done by motor drives. Feather touch push button switches for that purpose is very comfortably placed in each of the control panel. Actuate register can be easily attained and maintained with out much efforts for the operator.

## **Distributed Control Panel**

In normal machines the electrical controls of different drives are placed on a control panel which is separated from the machine and placed on the back of the operator side. The Rotogravure Printing Machine are very long in size, the operator has to come to the control panel for every operation of the control like on /off drives to boost up its power and down and the likewise operations. Similarly on emergency the operator has to run to the control panel to take immediate action. In Thaimadam Machine, the control panel is distributed through each printing unit and winding station. Almost all operations can be done from any control panel because clone switches are given for almost all operations. The operator can do any operation from any point where the operator is standing just by a stretch of hand.

The built-in distributed control panels are extremely comfortable for the operators. Almost all the basic operations on run-time can be done from any of the panel attached to each printing units. The operator can on / off any drive like winding drive, main-drive, dryer-air-circulators, lights etc., increase / decrease the winding torque, speed of main-drive etc., adjust web alignment etc., from any control panel. Power distribution is from very safe buss-bars supported by high quality MCB and circuit terminators. The electrical equipment like dimmer state, rectifiers etc. are isolated from machine and are enclosed in separate cabin placed suitably away from operation side. Necessary pilot lamps are provided so that the status of the machine and switches can be ascertained at any point of time.

**For further details please visit**

**[www.thaimadam.in](http://www.thaimadam.in) [www.thaimadam.com](http://www.thaimadam.com)**